

# CLICK LINEAR

## LINEAR SYSTEMS

IP20



\*Lighted space: 1.420 + 80 mm cover  
\*Espacio iluminado: 1.420 + 80 mm de tapa

| W    | mA  | TEMP    | LUM   | CRI |
|------|-----|---------|-------|-----|
| 36,3 | 500 | 3.000°K | 5.075 | >85 |
| 36,3 | 500 | 4.000°K | 5.525 | >85 |




85°

### CLICK LINEAR

**LED**  230V ≈ 36W | > 5.000lm **KLRX A 15 . . 9 A ..**

#### LED CONTROL

|  |                      |                               |
|--|----------------------|-------------------------------|
|  <b>N</b> | No Dimmable          | KLRX A .. <b>N</b> . . . . .. |
|  <b>D</b> | Dimmable Dali / Push | KLRX A .. <b>D</b> . . . . .. |

#### LED COLOUR TEMPERATURE

|  |         |                                 |
|--|---------|---------------------------------|
|  <b>3</b> | 3000° K | KLRX A .. . <b>3</b> . . . . .. |
|  <b>4</b> | 4000° K | KLRX A .. . <b>4</b> . . . . .. |

#### LED BEAM ANGLE

|  |           |                                 |
|--|-----------|---------------------------------|
|  <b>9</b> | Expansive | KLRX A .. . . . <b>9</b> . . .. |
|--|-----------|---------------------------------|

#### LED COMPLEMENTS

|  |              |                             |
|--|--------------|-----------------------------|
|  <b>A</b> | Ice Diffuser | KLRX A .. . . . <b>A</b> .. |
|--|--------------|-----------------------------|

#### COLOURS

|   |  |                           |
|---|--|---------------------------|
|  <b>WS</b> | Satin White<br><i>*Textured finished</i> | KLRX A .. . . . <b>WS</b> |
|  <b>BS</b> | Satin Black<br><i>*Textured finished</i> | KLRX A .. . . . <b>BS</b> |