



# CLICK STRAIGHT

## LINEAR SYSTEMS



	W	mA	TEMP	LUM	CRI
STRAIGHT 05	5.6	350	3.000K	1.270	>80
			4.000K	1.365	
STRAIGHT 10	15.9	350	3.000K	2.540	>80
			4.000K	2.730	

LED	230V	IP20	50.000h L90/B10	McAdam C3
500mm	≈ 5.6W > 1.200lm	<b>KST5 A 05</b>	• • • • •	• • • • •
1.000mm	≈ 16W > 2.500lm	<b>KST1 A 10</b>	• • • • •	• • • • •




### BASIC OPTIONS

<b>NO DIM</b>	<b>N</b>	No Dimmable								
<b>3K</b>	<b>3</b>	3000K								
<b>9</b>	<b>9</b>	120°								
<b>C</b>	<b>C</b>	Microprismatic diff.								
<b>WS</b>	<b>WS</b>	Satin White	KST5 A	<b>05</b>	<b>N</b>	<b>3</b>	<b>9</b>	<b>C</b>	<b>WS</b>	
			KST1 A	<b>10</b>	<b>N</b>	<b>3</b>	<b>9</b>	<b>C</b>	<b>WS</b>	
<b>BS</b>	<b>BS</b>	Satin Black	KST5 A	<b>05</b>	<b>N</b>	<b>3</b>	<b>9</b>	<b>C</b>	<b>BS</b>	
			KST1 A	<b>10</b>	<b>N</b>	<b>3</b>	<b>9</b>	<b>C</b>	<b>BS</b>	

### CUSTOMIZE OPTIONS

LED CONTROL										
<b>DALI</b>	<b>D</b>	Dimmable Dali	KST• A	•	<b>D</b>	•	9	C	•	•
<b>K</b>	<b>K</b>	Casambi	KST• A	•	<b>K</b>	•	9	C	•	•
<b>D</b>	<b>D</b>	Bluetooth	KST• A	•	<b>D</b>	•	9	C	•	•
LED COLOR TEMPERATURE										
<b>4K</b>	<b>4</b>	4000K	KST• A	•	•	<b>4</b>	9	C	•	•

### TEC.DRAWINGS



Para versión Bluetooth añadir Kit B.  
For Version Bluetooth please add the Kit B.