



OnLED IP 65 RECESSEDS



| | W | mA | TEMP | LUM | CRI |
|----------|---|-----|--------|-----|-----|
| OnLed 8W | 8 | 350 | 3.000K | 650 | >82 |
| | 8 | 350 | 4.000K | 720 | >82 |



≈ 8W > 600lm **OL65 A 08 . . 3 B ..**

BASIC OPTIONS

| | | | | | | | | | | |
|-----------------------|-----------|----------------|------|---|----|----------|----------|----------|----------|-----------|
| NO DIM | N | No Dimmable | | | | | | | | |
| 3K | 3 | 3000K | | | | | | | | |
| 30° - 40° | 3 | 30° - 40° | | | | | | | | |
| Clear Difusser | B | Clear Difusser | | | | | | | | |
| Satin White | WS | Satin White | OL65 | A | .. | N | 3 | 3 | B | WS |

CUSTOMIZE OPTIONS

| LED CONTROL | | | | | | | | | | |
|-------------|----------|---------------|------|---|----|----------|---|---|---|----|
| PUSH | F | Dimmable Push | OL65 | A | .. | F | . | . | . | .. |
| DALI | D | Dimmable Dali | OL65 | A | .. | D | . | . | . | .. |

TEC.DRAWINGS

